

Katalognummer	Höhe mm	Breite mm	Tiefe mm	Nennspannung	Maximaler Strom	Material	Plug Type	Noise Level	Einschaltstrom	Kühlkapazität, L35L35	Kühlkapazität, L35L50	Stromverbrauch, L35L35	Stromverbrauch, L35L50
NOX06C0E1U00009	640	316	240	115 V	4.6 A	Edelstahl	4-pin	65 dB(A)	22.2 A	720 W	555 W	380 W	450 W
NOX06C0E1U00000	640	316	240	115 V	4.6 A	Galv. Stahlblech	4-pin	65 dB(A)	22.2 A	720 W	555 W	380 W	450 W
NOX08C0E1U00009	640	316	240	115 V	4.8 A	Edelstahl	4-pin	65 dB(A)	22.2 A	880 W	705 W	450 W	520 W
NOX08C0E1U00000	640	316	240	115 V	4.8 A	Galv. Stahlblech	4-pin	65 dB(A)	22.2 A	880 W	705 W	450 W	520 W
NOX06B0E1U00009	640	316	240	230 V	2.3 A	Edelstahl	4-pin	65 dB(A)	10.9 A	720 W	555 W	380 W	450 W
NOX06B0E1U00000	640	316	240	230 V	2.3 A	Galv. Stahlblech	4-pin	65 dB(A)	10.9 A	720 W	555 W	380 W	450 W
NOX08B0E1U00009	640	316	240	230 V	2.4 A	Edelstahl	4-pin	65 dB(A)	12.9 A	880 W	705 W	450 W	520 W
NOX08B0E1U00000	640	316	240	230 V	2.4 A	Galv. Stahlblech	4-pin	65 dB(A)	12.9 A	880 W	705 W	450 W	520 W
NOX08K0E1C00009	640	316	240	400 V	1.4 A	Edelstahl	4-pin	65 dB(A)	7.4 A	880 W	705 W	450 W	520 W
NOX08K0E1C00000	640	316	240	400 V	1.4 A	Galv. Stahlblech	4-pin	65 dB(A)	7.4 A	880 W	705 W	450 W	520 W
NOX10C0E1U00009	783	348	220	115 V	6,00	Edelstahl	4-pin	65 dB(A)	28 A	1000 W	760 W	500 W	600 W
NOX10C0E1U00000	783	348	220	115 V	6,00	Galv. Stahlblech	4-pin	65 dB(A)	28 A	1000 W	760 W	500 W	600 W
NOX10B0E1U00009	783	348	220	230 V	3,00	Edelstahl	4-pin	65 dB(A)	13 A	1000 W	760 W	500 W	600 W
NOX10B0E1U00000	783	348	220	230 V	3,00	Galv. Stahlblech	4-pin	65 dB(A)	13 A	1000 W	760 W	500 W	600 W
NOX16C0E1U00009	1000	400	250	115 V	7,00	Edelstahl	4-pin	65 dB(A)	42 A	1600 W	1100 W	720 W	820 W
NOX16C0E1U00000	1000	400	250	115 V	7,00	Galv. Stahlblech	4-pin	65 dB(A)	42 A	1600 W	1100 W	720 W	820 W
NOX20C0E1U00009	1000	400	250	115 V	9,00	Edelstahl	4-pin	65 dB(A)	56 A	2000 W	1500 W	990 W	1130 W
NOX20C0E1U00000	1000	400	250	115 V	9,00	Galv. Stahlblech	4-pin	65 dB(A)	56 A	2000 W	1500 W	990 W	1130 W
NOX16B0E1U00009	1000	400	250	230 V	3,00	Edelstahl	4-pin	65 dB(A)	16 A	1600 W	1100 W	720 W	820 W
NOX16B0E1U00000	1000	400	250	230 V	3,00	Galv. Stahlblech	4-pin	65 dB(A)	16 A	1600 W	1100 W	720 W	820 W
NOX20B0E1U00009	1000	400	250	230 V	4,00	Edelstahl	4-pin	65 dB(A)	21 A	2000 W	1500 W	990 W	1130 W
NOX20B0E1U00000	1000	400	250	230 V	4,00	Galv. Stahlblech	4-pin	65 dB(A)	21 A	2000 W	1500 W	990 W	1130 W
NOX12K0E1C00009	1000	400	250	400 V	1,00	Edelstahl	4-pin	65 dB(A)	9:00 AM	1250 W	930 W	590 W	680 W
NOX12K0E1C00000	1000	400	250	400 V	1,00	Galv. Stahlblech	4-pin	65 dB(A)	9:00 AM	1250 W	930 W	590 W	680 W
NOX40B0E1U00009	1270	500	336	230 V	7,00	Edelstahl	4-pin	70 dB(A)	37 A	3850 W	2650 W	1670 W	1980 W